

Futura HD 150 Brattpan Model - Futura HD (3756283)

STANDARD FEATURES

- Stainless steel frying surface
- Elevated control pillar
- Aluminum encased flat heating elements
- Temperature control to 250°C
- 2-zone heating
- Water filling to pan.
- Electric tilting motor.
- Depth 273mm
- 3 GN format
- Construction of AISI 304 and 403 stainless steel
- Insulated and balanced lid
- Rounded corners of inner pan
- Recoiled hand-shower
- Emergency all stop control button.



Net Volume Geo Volume Dimensions	150L 170L	Connections Water Electrical	Cold ø3/4"	Waste Net Weight	By kitchen contractor 320 kg	Frying surface – 0.59m ² Power of Single Heating element 2.3 kW
Width Height Depth	1553 mm 1559mm 955mm	Electrical	Power 27,6 kW Voltage 400V, 3P+N+E 50/60Hz AMP 50A			
						2 94 94 94 94 94 94 94 94 94 94 94 94 94 94 94 94 94 94 94 94 94 94 94 94 94 94 94 94 94 94 94 94 94 94 94 950 min 500 min 500 (distance for maintenance)
Finland metos.com/manufacturing				 Cable gland PG36 for electrical supply cable. Reserve 1,0m of power cable above floor level. Cold water connection G3/4, one- way valve must be fitted. Valve not 		
Metos Oy Ab Ahjonkaarre Fl 04220 Kerava Finland Telephone +358 204 3913				included in deli 3. All four feet delivery.	very. should be fixed to	o the floor. Mounting screws not included in ation manual must be followed.

Disclaimer: All unit capacities are based on subjective testing.

In line with policy to continually develop and improve its products, Metos Oy Ab reserves the right to change specifications and design without notice.

international.sales@metos.com

